CAT 908 demo 2024 CE EPA 40k/hr bucket forks qc 220 hr

Amount of previous

owners

Attachments

Body type

Brand

Bucket capacity cm3

Cabin type

Certificates

Condition

Condition info/guarantee

Country

Delivery terms

Emission level

Engine

Engine manufacturer

Engine output hp

Front tyres remaining %

Full service history

General grade (1 min - 5

max)

Gross Weight kg























Inspection report

Internal stock no.

Latest inspection

Machine location

Manufacturing / Serial

number

Maximum lift capacity kg

Model

Model description

Original colour

Other information

one [1] pc Caterpillar 908 wheelloader year 2024 with 220 hours only 3 rd hydr valve quick coupler set forks GP bucket with straight edge fast runner 40 km/hr cabin with climate control air conditioning airsuspended driverseat original colour worklights toolbox beacon factory CE certified factory EPA certified made in United Kingdom washed, cleaned and workshop tested immaculate condition Price each ex works Haaften The Netherlands Configured for Success Cat® wheel loaders set the standard for productivity, fuel efficiency and operator comfort. The Cat 908 Compact Wheel Loader has a high torque C2.8 engine that works in conjunction with an intelligent hystat power





RIVERLAND EQUIPMENT BV

Hertog Karelweg 21 NL 4175 LS Haaften The Netherlands

T: +31 418 654000 F: +31 418 651623

E: info@riverlandequipment.com E: sales@riverlandequipment.com train to deliver exceptional fuel efficiency. "Shift on the go" locking differentials and hydrostatic transmission provide smooth and powerful operation while increasing the efficiency of machine cycles. Benefits 60% Greater Wiper Coverage all new cab with seat mounted controls and integrated display screen 40 kph (25 mph) with "shift on the go" transmission Customized for application specific configurations including factory and aftermarket options Cat® wheel loaders set the standard for productivity, fuel efficiency and operator comfort. The Cat 908 Compact Wheel Loader has a high torque C2.8 engine that works in conjunction with an intelligent hystat power train to deliver exceptional fuel efficiency. Dependent on regional requirements our engines emit equivalent to EU Stage IIIA (U.S. EPA Tier 3) or meets EU Stage V (U.S. EPA Tier 4 Final) with a clean emission module designed to manage itself so you can concentrate on the task at hand.

Output of the auxiliary hydraulics Power type Product link

Production country

I/min

Rear tyres remaining

%

Registration number

Top speed km/h

Transport dimensions

m

(LxWxH)

Tyre brand

Year of manufacture